

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 30 October 2003 (30.10.2003)

(10) International Publication Number WO 03/090336 A1

(51) International Patent Classification7:

H02M 1/15

(21) International Application Number: PCT/DK03/00260

(22) International Filing Date: 16 April 2003 (16.04.2003)

(25) Filing Language:

Danish

(26) Publication Language:

English

(30) Priority Data:

PA2002 00581 19 April 2002 (19.04.2002) DK PA2002 00589 19 April 2002 (19.04.2002) DK PA2002 00595 19 April 2002 (19.04.2002) DK

(71) Applicant (for all designated States except US): LINAK A/S [DK/DK]; Smcdcvænget 8, Guderup, DK-6430 Nordborg (DK).

(72) Inventor; and

(75) Inventor/Applicant (for US only): BASTHOLM, Jeppe [DK/DK]; Bækgade 3, Blans, DK-6400 Sønderborg (DK).

(74) Agent: LINAK A/S; Patent Department, P.O. Box 238, DK-9100 Aalborg (DK).

(81) Designated States (national): AE, AG, AL, AM, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CII, CN, CO, CR, CU, CZ (utility model), DE (utility model), DK (utility model), DM, DZ, EC, EE (utility model), ES, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: Λ DRIVE UNIT, PREFERABLY ΛΝ ΛCTUΛΤΟR, Λ CONTROL ΛΝD Λ CONSTRUCTION

(57) Abstract: In particular in articles of furniture having at least an element which may be adjusted with a DC motor, preferably via a mechanical transmission, it is desirable to have a level of acoustic noise as low as possible. The power supply to the DC motor is based on a transformer with rectification and smoothing. With the invention it has surprisingly been found that the level of acoustic noise may be reduced significantly in that the secondary side of the transformer has a first control to compensate for the loss in the motor, thereby keeping the speed thereof constant for a long period of time, and a second control adapted to remove the ripple in the voltage, thereby keeping the speed of the motor constant for a short period of time.